

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 October 2004 (14.10.2004)

PCT

(10) International Publication Number
WO 2004/087626 A1

(51) International Patent Classification⁷: **C07C 5/333**,
C10G 11/00, 11/22, C07C 11/02, 11/04, 11/06

(21) International Application Number:
PCT/GB2004/001278

(22) International Filing Date: 24 March 2004 (24.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0307759.1 3 April 2003 (03.04.2003) GB
0329346.1 18 December 2003 (18.12.2003) GB

(71) Applicant (for all designated States except US): **BP CHEMICALS LIMITED** [GB/GB]; Chertsey Road, Sunbury-on-Thames, Middlesex TW16 7BP (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LITTLE, Ian, Raymond** [GB/GB]; 188 Manor Road North, Thames Ditton, Surrey KT7 0BQ (GB). **MAUNDERS, Barry, Martin** [GB/GB]; "Woodlands", 5 Paddock Way, Woodham, Woking, Surrey GU21 5TB (GB). **MESSENGER, Brian, Edward** [GB/GB]; 76 Wild Herons, Hook, Hampshire RG27 9SF (GB).

(74) Agent: **HYMERS, Ronald, Robson**; BP International Limited, Patents & Agreements, Chertsey Road, Sunbury-on-Thames, Middlesex TW16 7LN (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,

KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW. ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: AUTOTHERMAL CRACKING PROCESS

(57) Abstract: The present invention provides a process for the production of olefins which process comprises co-feeding at least one unsaturated hydrocarbon with a paraffinic hydrocarbon-containing feedstock and a molecular oxygen-containing gas to an autothermal cracker, wherein they are reacted in the presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising olefins.

WO 2004/087626 A1

1/28/05

AUTOTHERMAL CRACKING PROCESS

The present invention relates to the production of mono-olefins by autothermal cracking of a paraffinic hydrocarbon having two or more carbon atoms especially autothermal cracking of ethane, propane, and butanes.

Olefins such as ethene and propene may be produced by a variety of processes including the steam cracking of hydrocarbons or by the dehydrogenation of paraffinic feedstocks. More recently, it has been disclosed that olefins may be produced by a process known as auto-thermal cracking. In such a process a paraffinic hydrocarbon feed is mixed with an oxygen-containing gas and contacted with a catalyst which is capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising olefins. The hydrocarbon feed is partially combusted and the heat produced is used to drive the dehydrogenation reaction. Such a process is described, for example, in EP-B1-0332289.

The steam cracking of hydrocarbons to produce mono-olefins normally co-produces other unsaturated hydrocarbons e.g. dienes and alkynes.

The dienes are usually separated from the steam cracker product stream which involves the use of large amounts of toxic flammable solvents e.g. acetonitrile. Once separated the dienes are considered high value products and are used in derivative processes e.g. elastomer production. However dienes are difficult to transport because they are readily degraded via oligomerisation and consequently derivative plants that employ diene feedstock are usually co-located with the sources of supply. Where there is no derivative capacity to use the dienes the production of dienes becomes problematic. This is because it is not desirable that dienes be recycled to a steam

cracker due to their high propensity to cause carbonaceous fouling of the process equipment and therefore the dienes must be hydrogenated before being recycled to the steam cracker, or short furnace run-times must be tolerated, with consequent financial and operational disadvantages.

5 Similar problems arise with other unsaturated hydrocarbons produced by steam cracking, such as alkynes. These also have a high propensity to cause carbonaceous fouling if recycled to a steam cracker, and therefore must be hydrogenated before recycling, or short furnace run-times must be tolerated.

10 It has now been found that the autothermal cracking process can tolerate co-feeding unsaturated hydrocarbons without carbonaceous fouling, and therefore unsaturated hydrocarbons can be fed without causing reduced run-times. More particularly, it has now been found that the autothermal cracking process can be improved by co-feeding at least one unsaturated hydrocarbon, in particular a diene or alkyne, with the paraffinic hydrocarbon feed and the molecular oxygen-containing gas to the autothermal cracker. It has been found that co-feeding at least one unsaturated
15 hydrocarbon can provide an increase in the olefin yield based on the amount of paraffinic hydrocarbon feed converted. Without wishing to be bound by theory, this is believed to be due to the propensity of co-fed unsaturated hydrocarbons to combust in preference to paraffinic hydrocarbons in the feed. Furthermore it has been found that the
20 majority of the unsaturated hydrocarbon can be converted and, surprisingly, no significant carbon formation occurs on the catalyst, and unexpectedly low amounts of additional compounds e.g. benzene or toluene, associated with carbon formation on the catalyst are produced.

25 Accordingly the present invention provides a process for the production of olefins which process comprises feeding (i) a paraffinic hydrocarbon-containing feedstock, (ii) at least one unsaturated hydrocarbon and (iii) a molecular oxygen-containing gas to an autothermal cracker, wherein they are reacted in the presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising olefins.

30 "Unsaturated hydrocarbon", as used herein, includes olefins.

Thus, the unsaturated hydrocarbon may be an alkene such as ethene, propene, butenes, pentenes, hexenes, heptenes, higher alkenes and cycloalkenes, such as

cyclopropene, cyclobutene, cyclopentene(s), cyclohexene(s), cycloheptenes and higher cycloalkenes.

The unsaturated hydrocarbon may be an aromatic compound. Suitable aromatic compounds include benzene, toluene, xylenes, ethylbenzene, styrene and substituted styrenes, indene and substituted indenenes. Where the autothermal cracker is operated at relatively low pressures, typically atmospheric pressure up to 5 barg, the preferred aromatic compounds are xylenes, indenenes and styrenes. Where the autothermal cracker is operated at higher pressures, typically above 5 barg, the preferred aromatic compounds are benzene and/or toluene.

In a first preferred embodiment the unsaturated hydrocarbon is a diene. The diene(s) may be selected from any suitable dienes but are preferably selected from propadiene, 1,2 butadiene, 1,3 butadiene, 1,3 pentadiene, 1,4 pentadiene, cyclopentadiene, 1,3 hexadiene, 1,4 hexadiene, 1,5 hexadiene, 2,4 hexadiene, 1,3 cyclohexadiene and 1,4 cyclohexadiene, and substituted derivatives of the above, e.g. alkyl substituted derivatives, e.g. methyl derivatives with more than one substitution per molecule, wherein the substituents may be the same or different. Most preferably the diene(s) are selected from 1,2 butadiene, 1,3 butadiene, 2 methyl 1,3 butadiene, 1,3 pentadiene, 1,4 pentadiene and cyclopentadiene. Advantageously the diene is 1,3 butadiene.

In a second preferred embodiment, the unsaturated hydrocarbon may be an alkyne such as acetylene, propyne and/or a butyne. A particularly preferred alkyne is acetylene.

A single unsaturated hydrocarbon or a mixture of unsaturated hydrocarbons may be fed to the autothermal cracker.

The process for the production of olefins according to the present invention produces predominantly mono-olefins (alkenes), especially ethene and propene, although quantities of other olefins may also be produced.

Although alkenes may be co-fed without carbonaceous fouling of the process, and may be expected to combust in preference to paraffinic hydrocarbons in the feed, it is generally preferred not to co-feed alkenes which are the same as the desired products of the process. However, co-feed of alkenes which are the same as the desired products of the process may take place if they are present as part of a stream also comprising

other unsaturated hydrocarbons. Alternatively, for example, although it is generally preferred not to co-feed ethene and/or propene to an autothermal cracker for the production of predominantly ethene and/or propene, it may be advantageous to co-feed other alkenes, such as butenes, even if said process also produces said other alkenes.

5 In addition, co-feed of alkenes, such as ethene and propene, may also be advantageous where the alkene is present as unreacted alkene in an off-gas stream, which may also comprise alkane, of an alkene derivative process. Thus, ethene may be present in the off-gas of an ethene derivative process, such as a polyethylene process, an ethylbenzene process, an ethanol process and a vinyl acetate process. Propene may be
10 present in the off-gas of a propene derivative process, such as a polypropylene process, an acrolein process, an iso-propanol process and an acrylic acid process.

Preferably, therefore, the unsaturated hydrocarbon fed to the autothermal cracker process of the present invention comprises at least one unsaturated hydrocarbon other than an alkene, such as at least one of a diene and an alkyne. More preferably, there is
15 fed to the autothermal cracker at least one unsaturated hydrocarbon other than an alkene and less than 1wt%, such as less than 0.5wt%, of individual alkenes, such as ethene and propene, based on the weight of paraffinic hydrocarbon fed to the reactor. Even more preferably, there is fed to the autothermal cracker at least one unsaturated hydrocarbon other than an alkene and less than 1wt%, such as less than 0.5wt% of total alkenes,
20 based on the weight of paraffinic hydrocarbon fed to the reactor. Most preferably, the feed to the autothermal cracker comprises at least one of a diene and an alkyne, and has a substantial absence of alkene.

In an alternative embodiment, the unsaturated hydrocarbon fed to the autothermal cracker process of the present invention may comprise at least one
25 unsaturated hydrocarbon other than an aromatic compound.

The unsaturated hydrocarbon is provided as a separate feedstock than the paraffinic hydrocarbon-containing feedstock. However, it should be noted that the paraffinic hydrocarbon-containing feedstock may also contain unsaturated hydrocarbons, and the unsaturated hydrocarbon-containing feedstock may also contain
30 paraffinic hydrocarbons.

The unsaturated hydrocarbon may derive from the product stream of a conventional steam cracking reactor. Alternatively the unsaturated hydrocarbon may

derive from the off gas stream of a fluid catalytic cracking reactor or may derive from the off gas streams of a delayed coker unit, a visbreaker unit or an alkylation unit. The unsaturated hydrocarbon may also be provided as a refinery stream derived from a coker, fluid catalytic cracking (FCC) or residue catalytic cracking (RCC) units.

5 In addition the unsaturated hydrocarbon may be provided by a plastics recycling process e.g. pyrolytic polymer cracking.

In one embodiment of the present invention the unsaturated hydrocarbon is provided as a portion of the product stream from a polymer cracking reactor. As well as unsaturated hydrocarbons, the product stream from the polymer cracking reactor may
10 also comprise paraffinic hydrocarbons and, hence, may also provide at least a portion of the total paraffinic hydrocarbon fed to the process of the present invention.

The autothermal cracking reactor produces a product stream comprising unsaturated hydrocarbons (olefins and other unsaturated hydrocarbons). In a preferred embodiment of the invention the unsaturated hydrocarbon fed to the autothermal
15 cracking reactor derives from the autothermal cracking product stream.

Consequently the present invention also provides a process for the production of olefins which process comprises the steps of:

- (a) feeding a paraffinic hydrocarbon-containing feedstock and a molecular oxygen-containing gas to an autothermal cracker wherein they are reacted in the
20 presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising olefins
- (b) recovering at least a portion of the olefins produced in step (a) and
- (c) recycling at least one unsaturated hydrocarbon produced in step (a) back to the autothermal cracker.

25 In one preferred embodiment, the hydrocarbon product stream produced in step (a) is separated into a first stream comprising hydrocarbons containing less than 4 carbon atoms and a second stream comprising hydrocarbons containing at least 4 carbon atoms.

Consequently a further embodiment of the invention provides a process for the
30 production of ethene and/or propene which process comprises the steps of:

- (a) feeding a paraffinic hydrocarbon-containing feedstock and a molecular oxygen-containing gas to an autothermal cracker wherein they are reacted in the presence of a

catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising ethene and/or propene

- (b) separating the hydrocarbon product stream produced in step (a) into a first stream comprising hydrocarbons containing less than 4 carbon atoms and a second stream comprising hydrocarbons containing at least 4 carbon atoms, including at least one unsaturated hydrocarbon containing at least 4 carbon atoms
 - (c) recovering ethene and/or propene from the first stream and
 - (d) recycling at least a portion of the second stream to the autothermal cracker.
- 10 In this embodiment, preferably the unsaturated hydrocarbon containing at least 4 carbon atoms is recovered from the second stream and recycled to the autothermal cracker.

The unsaturated hydrocarbon containing at least 4 carbon atoms may be any unsaturated compound as herein described above containing at least 4 carbon atoms. Preferably the unsaturated hydrocarbon containing at least 4 carbon atoms is selected from 1,2 butadiene, 1, 3 butadiene, 2 methyl 1,3 butadiene, 1,3 pentadiene, 1,4 pentadiene and cyclopentadiene and is advantageously 1, 3 butadiene.

As stated above, in a second preferred embodiment the unsaturated hydrocarbon may be an alkyne such as acetylene, propyne and/or a butyne.

Consequently, the present invention also provides a process for the production of ethene and/or propene which process comprises the steps of:

- (a) feeding a paraffinic hydrocarbon-containing feedstock and a molecular oxygen-containing gas to an autothermal cracker wherein they are reacted in the presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising ethene and/or propene, and at least one alkyne
- (b) recovering at least a portion of the ethene and/or propene produced in step (a) and
- (c) recycling at least a portion of the at least one alkyne produced in step (a) back to the autothermal cracker.

30 In this preferred embodiment, it has been found that co-feeding at least one alkyne can provide significant improvements in ethene yield and, in addition, that co-feeding alkynes can suppress methane yield.

A single alkyne or a mixture of alkynes may be passed to the autothermal cracker. Alternatively, a mixture of one or more alkynes with one or more other unsaturated compounds, such as one or more alkenes and/or dienes, may be passed to the autothermal cracker.

5 As stated above, at least a portion of the unsaturated hydrocarbon derives from the autothermal cracking product stream itself i.e. from the hydrocarbon product stream. If required, the unsaturated hydrocarbon derived from the hydrocarbon product stream may be supplemented by additional unsaturated hydrocarbon from one or more other sources, such as from the product stream of a conventional steam cracking reactor, the
10 off gas stream of a fluid catalytic cracking reactor, the off gas streams of a delayed coker unit, a visbreaker unit or an alkylation unit or from a plastics recycling process e.g. pyrolytic polymer cracking.

Where the unsaturated hydrocarbon is an alkyne (or mixture comprising at least one alkyne), a particularly preferred source of supplemental alkyne, where required, is
15 acetylene obtained by acetylene generation from methane. Such acetylene generation processes are well-known, and include, for example, oxidative and non-oxidative pyrolysis and oxidative coupling processes. Most preferably, the methane for the acetylene generation may itself be derived from the autothermal cracking product stream, giving an overall process in which at least some of any methane formed in the
20 autothermal cracking process is converted to acetylene, which is then co-fed back to the autothermal cracking process to improve olefin yield and suppress formation of further methane. Hence, when the unsaturated hydrocarbon is an alkyne the present process can provide significant benefit (i.e. reduction) in the overall selectivity to methane.

The paraffinic hydrocarbon-containing feedstock may suitably be ethane,
25 propane or butane, or a mixture thereof. The hydrocarbon-containing feedstock may comprise other hydrocarbons and optionally other materials, for example, nitrogen, carbon monoxide, carbon dioxide, steam or hydrogen. In particular, the paraffinic hydrocarbon-containing feedstock may also contain unsaturated hydrocarbons, such as olefins and aromatics, in addition to the at least one unsaturated hydrocarbon feedstock.

30 The paraffinic hydrocarbon-containing feedstock may contain a fraction such as naphtha, gas oil, vacuum gas oil, or mixtures thereof. Usually the paraffinic hydrocarbon-containing feedstock comprises a mixture of gaseous paraffinic

hydrocarbons, principally comprising ethane, resulting from the separation of methane from natural gas.

The paraffinic hydrocarbon-containing feedstock, the at least one unsaturated hydrocarbon and the molecular oxygen-containing gas may all be passed as
5 separate streams to the autothermal cracker.

Usually the at least one unsaturated hydrocarbon is pre-mixed with the paraffinic hydrocarbon-containing feedstock and subsequently passed to the autothermal cracker. The resultant stream usually has the unsaturated hydrocarbon at a weight percentage of at least 0.01 wt%, preferably at least 0.1 wt%, most preferably at least 1 wt% and
10 advantageously at least 2 wt% based on the weight of paraffinic hydrocarbon.

Usually the unsaturated hydrocarbon has a weight percentage of between 0.01-50 wt%, preferably between 0.1-30 wt%, most preferably between 1-20wt% and advantageously between 2-15wt% based on the weight of the paraffinic hydrocarbon.

Where the unsaturated hydrocarbon is a diene (or mixture comprising at least
15 one diene), the unsaturated hydrocarbon preferably has a weight percentage of between 1-20 wt% of diene, preferably between 2-15 wt% of diene, based on the weight of the paraffinic hydrocarbon.

Where the unsaturated hydrocarbon is an alkyne (or mixture comprising at least one alkyne), the unsaturated hydrocarbon preferably has a weight percentage of between
20 0.1-5wt% of alkyne, preferably between 1-5 wt% of alkyne, based on the weight of the paraffinic hydrocarbon.

The molecular oxygen-containing gas may suitably be either oxygen or air. Preferably the molecular oxygen-containing gas is oxygen, optionally diluted with an inert gas, for example nitrogen.

25 The ratio of paraffinic hydrocarbon-containing feedstock to molecular oxygen-containing gas mixture is suitably from 5 to 13.5 times the stoichiometric ratio of hydrocarbon to oxygen-containing gas for complete combustion to carbon dioxide and water. The preferred ratio is from 5 to 9 times the stoichiometric ratio of hydrocarbon to oxygen-containing gas.

30 Additional feed streams comprising at least one from carbon monoxide, carbon dioxide, steam and hydrogen may also be passed to the autothermal cracker. Preferably an additional feed stream comprising hydrogen is passed to the

autothermal cracker. Preferably the additional feed stream comprising hydrogen is pre-mixed with the paraffinic hydrocarbon-containing feedstock and subsequently passed to the autothermal cracker.

The autothermal cracker may suitably be operated at a temperature greater than 500°C, for example greater than 650°C, typically greater than 750°C, and preferably greater than 800°C. The upper temperature limit may suitably be up to 1200°C, for example up to 1100°C, preferably up to 1000°C.

In general, the autothermal cracker may be operated at atmospheric or elevated pressure. Pressures of 1-40 barg may be suitable, preferably a pressure of 1-5 barg e.g. 1.8 barg is employed. However a total pressure of greater than 5 barg may be used, usually a total pressure of greater than 15 barg. Advantageously the autothermal cracker is operated in a pressure range of between 15-40 barg, such as between 20-30 barg e.g. 25 barg.

Where the unsaturated hydrocarbon is an alkene, an aromatic compound or a mixture of alkenes and/or aromatic compounds, the autothermal cracker is preferably operated at a total pressure of greater than 5 barg, usually a total pressure of greater than 15 barg, and advantageously in a pressure range of between 15-40 barg, such as between 20-30 barg e.g. 25 barg.

Preferably, the paraffinic hydrocarbon-containing feedstock, the gas comprising at least one unsaturated hydrocarbon and the molecular oxygen-containing gas are fed to the autothermal cracker in admixture under a Gas Hourly Space Velocity (GHSV) of greater than 80,000 hr⁻¹. Preferably, the GHSV exceeds 200,000 hr⁻¹, especially greater than 1,000,000 hr⁻¹. For the purposes of the present invention GHSV is defined as:-
(volume of total feed at NTP / hour) / (volume of catalyst bed).

Suitably the catalyst is a supported platinum group metal. Preferably, the metal is either platinum or palladium, or a mixture thereof. Where the unsaturated hydrocarbon is an alkyne (or mixture comprising at least one alkyne), the metal preferably comprises a mixture of platinum and palladium

Although a wide range of support materials is available, it is preferred to use alumina as the support. The support material may be in the form of spheres, other granular shapes or ceramic foams. Preferably, the foam is a monolith which is a continuous multichannel ceramic structure, frequently of a honeycomb appearance. A

preferred support for the catalytically active metals is a gamma alumina. The support is loaded with platinum and/or palladium by conventional methods well known to those skilled in the art. Advantageously catalyst promoters may also be loaded onto the support. Suitable promoters include copper and tin. Usually the products are quenched
5 as they emerge from the autothermal cracker such that the temperature is reduced to less than 650°C within less than 150 milliseconds of formation.

Where the pressure of the autothermal cracker is maintained at a pressure of between 1.5-2.0 barg usually the products are quenched and the temperature reduced to less than 650°C within 100-150 milliseconds of formation.

10 Where the pressure of the autothermal cracker is maintained at a pressure of between 2.0-5.0 barg usually the products are quenched and the temperature reduced to less than 650°C within 50-100 milliseconds of formation.

Where the pressure of the autothermal cracker is maintained at a pressure of between 5.0-10.0 barg usually the products are quenched and the temperature reduced to
15 less than 650°C within less than 50 milliseconds of formation.

Where the pressure of the autothermal cracker is maintained at a pressure of between 10.0-20.0 barg usually the products are quenched and the temperature reduced to less than 650°C within 20 milliseconds of formation.

Finally where the pressure of the autothermal cracker is maintained at a pressure
20 of greater than 20.0 barg usually the products are quenched and the temperature reduced to less than 650°C within 10 milliseconds of formation.

This avoids further reactions taking place and maintains a high olefin selectivity.

The products may be quenched using rapid heat exchangers of the type familiar in steam cracking technology. Additionally or alternatively, a direct quench may be
25 employed. Suitable quenching fluids include water.

The present invention usually provides a percentage conversion of gaseous paraffinic hydrocarbon of greater than 40%, preferably greater than 50%, and most preferably greater than 60%.

Furthermore the present invention usually provides a selectivity towards mono-
30 olefins of greater than 50%, preferably greater than 60%, and most preferably greater than 70%.

In a further aspect of the present invention, there is provided a process for the

production of olefins which process comprises feeding a paraffinic hydrocarbon, at least one unsaturated hydrocarbon and a molecular oxygen-containing gas to an autothermal cracker wherein they are reacted in the presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising olefins, said process being characterised in that the total hydrocarbon fed to the autothermal cracker comprises at least 20wt% of unsaturated hydrocarbons.

In this aspect of the present invention, both the paraffinic hydrocarbon and the at least one unsaturated hydrocarbon may be provided as a single hydrocarbon-containing feedstock comprising at least 20wt% of unsaturated hydrocarbons. For example, the single hydrocarbon-containing feedstock may be a stream boiling in the middle distillate range (typically 150°C to 400°C) or in the naphtha-range (typically 30°C to 220°C), but with significantly higher unsaturated hydrocarbon content than would conventionally be fed to a steam cracker (without considerable dilution by saturated feeds from other sources). Suitable feedstocks include refinery streams derived from coker, fluid catalytic cracking (FCC) or residue catalytic cracking (RCC) units.

Because of the ability of the autothermal cracker to tolerate significant quantities of unsaturated hydrocarbons without carbonaceous fouling, streams which would not conventionally be considered for steam cracking (without considerable dilution by saturated feeds from other sources) can be readily fed to the autothermal cracker. The removal of constraint on the unsaturated hydrocarbon content of the hydrocarbon-containing feedstock, may also allow processes which conventionally generate cracking feedstocks, such as crude oil distillation to produce straight-run naphtha, to be operated more advantageously.

Preferably the total hydrocarbon fed to the autothermal cracker comprises 20 to 70wt%, such as 25 to 50wt%, of unsaturated hydrocarbons. Typically, the unsaturated hydrocarbons may comprise olefins, such as at least 10wt% olefins, and aromatics, such as at least 10wt% aromatics. As used in this aspect, the percent by weight (wt%) is based on the total weight of hydrocarbons in the combined feeds to the autothermal cracker.

The invention will now be illustrated in the following examples and Figure 1. Figure 1 represents a schematic view of an autothermal cracking apparatus.

Figure 1 depicts an autothermal cracking apparatus comprising a quartz reactor, 1, surrounded by an electrically-heated furnace, 2. The reactor, 1, is coupled to an oxygen-containing gas supply, 3, and a hydrocarbon feed supply, 4 (for both the paraffinic hydrocarbon and unsaturated hydrocarbon). The hydrocarbon feed supply, 4, is pre-heated in an electrically heated furnace, 5. Optionally, the hydrocarbon feed may comprise a further co-feed such as hydrogen and a diluent such as nitrogen. In use, the reactor, 1, is provided with a catalyst zone, 6, which is capable of supporting combustion beyond the fuel rich limit of flammability and comprises a catalyst bed, 7. The catalyst bed, 7, is positioned between heat shields, 8, 9.

In use, the furnace, 2, is set so as to minimise heat losses. As the reactants contact the catalyst bed, 7, some of the hydrocarbon feed combusts to produce water and carbon oxides. The optional hydrogen co-feed also combusts to produce water. Both of these combustion reactions are exothermic, and the heat produced therefrom is used to drive the cracking of the hydrocarbon to produce olefin.

Examples

Catalyst A

An auto-thermal cracking catalyst comprising 3wt% platinum and 1wt% copper deposited on an alumina foam (15mm diameter x 30mm deep, 30 pores per inch supplied by Vesuvius Hi-Tech Ceramics, Alfred, NY USA) was prepared by repeated impregnation with solutions of tetraamineplatinum (II) chloride and copper (II) chloride in deionised water. The metal salt solutions were of sufficient concentration to achieve the desired loadings of Pt and Cu if all the metal salt were incorporated into the final catalyst formulation. After each impregnation, any excess solution was removed, and the alumina foam was dried in air at 120°C-140°C and calcined in air at 450°C before the next impregnation. Once all the solution had been adsorbed, the foams were dried and reduced under hydrogen/nitrogen atmosphere at 650-700°C for 1 hour.

Catalyst B

An auto-thermal cracking catalyst comprising platinum and palladium deposited on alumina spheres was prepared by impregnation, using incipient wetness, of 100g of alumina spheres (supplied by Condea, 1.8mm diam. alumina spheres, Surface Area 210 m²/g), with a solution containing 4.415g of tetraamineplatinum (II) chloride and 0.495g

of tetraaminepalladium (II) chloride in deionised water. The spheres were dried at 120°C for 1 hour and then calcined, in air, at 1200°C for 6 hours.

Example 1

The auto-thermal cracking catalyst comprising platinum and copper deposited on alumina foam (two blocks of Catalyst A resulting in a bed 60mm deep) was placed in the autothermal cracker and the cracker was heated to 850°C.

A feed stream comprising ethane, nitrogen and hydrogen was passed to the autothermal cracker. Oxygen was then passed to the autothermal cracker to initiate the reaction. The hydrogen to oxygen volume ratio was maintained at 1.9:1 (v/v). The reaction was performed at atmospheric pressure.

Samples were analysed at oxygen to ethane feed ratios of 0.35, 0.44, 0.53 and 0.61 (v/v).

The nitrogen was then replaced with a feed stream comprising 9.65 volume % of 1, 3 butadiene in nitrogen and the analysis repeated.

The % conversion of ethane and the selectivity towards ethylene was measured and the results are shown in table 1.

Example 2

Example 1 was repeated using a hydrogen to oxygen volume ratio of 1:1 (v/v). The % conversion of ethane and the selectivity towards ethylene was measured and the results are shown in table 2.

Example 3

Example 1 was repeated using a hydrogen to oxygen volume ratio of 0.5:1 (v/v)

The samples were taken at oxygen to ethane feed ratios of 0.35, 0.44, and 0.53 (v/v). The % conversion of ethane and the selectivity towards ethylene was measured and the results are shown in table 3.

Table1

Autothermal cracking of ethane and ethane with butadiene over a Pt-Cu catalyst with a hydrogen to oxygen volume ratio of 1.9:1 (v/v).

	ethane butadiene	ethane butadiene	ethane butadiene	ethane butadiene	ethane butadiene	ethane butadiene	ethane butadiene	
Total feed rate nl/min	9.03	9.02	9.19	9.18	9.18	9.17	9.16 9.11	
O2 : C2H6 (v/v)	0.353	0.353	0.435	0.435	0.527	0.527	0.605 0.605	
H2:O2 (v/v)	1.994	1.986	1.958	1.969	1.868	1.886	1.841 1.826	
N2:O2 (v/v)	0.543	0.490	0.492	0.433	0.446	0.387	0.426 0.375	
1,3-butadiene : ethane (v/v)	---	0.020	---	0.022	---	0.024	---	0.027
Ethane conversion (%)	46.00	42.87	58.74	55.88	74.76	72.19	84.65	82.40
Oxygen conversion (%)	98.42	98.12	98.30	98.42	98.48	98.75	98.73	98.84
Butadiene Conversion (%)	---	93.05	---	96.24	---	97.66	---	100.00
Ethene yield (g per 100g ethane feed)	36.50	35.59	44.93	44.87	53.16	54.13	55.87	57.93
Aromatics yield (g per 100g ethane feed)	0.03	0.08	0.03	0.04	0.14	0.02	0.22	0.02
Ethene selectivity (g per 100g ethane converted)	79.35	83.03	76.49	80.29	71.11	74.98	66.00	70.30

Table 2:

Autothermal cracking of ethane and ethane with butadiene over a Pt-Cu catalyst with a hydrogen to oxygen volume ratio of 1:1 (v/v).

5

	ethane butadiene	ethane butadiene	Ethane butadiene	ethane butadiene	ethane butadiene	ethane butadiene	ethane butadiene	
Total feed rate (nl/min)	7.62	7.62	7.77	7.76	7.76	7.74	7.71 7.66	
O2 : C2H6 (v/v)	0.353	0.353	0.435	0.435	0.527	0.527	0.602 0.602	
H2:O2 (v/v)	0.996	0.994	1.069	1.068	1.055	1.048	1.058 1.046	
N2:O2 (v/v)	0.538	0.484	0.483	0.433	0.443	0.400	0.431 0.378	
1,3-butadiene : ethane (v/v)	---	0.021	---	0.023	---	0.026	---	0.028
ethane conversion (%)	47.86	46.15	60.97	59.14	77.10	75.43	86.44	84.98
oxygen conversion (%)	98.80	98.69	98.85	98.74	98.82	98.79	98.94	98.97
butadiene conversion (%)	---	92.86	---	92.01	---	97.47	---	98.37
Ethene yield (g/100g ethane feed)	35.59	36.14	44.10	44.98	52.13	53.58	54.35	56.33
Aromatics yield (g per 100g ethane feed)	0.03	0.03	0.02	0.05	0.03	0.13	0.10	0.13
Ethene selectivity (g per 100g ethane converted)	74.36	78.31	72.33	76.06	67.61	71.03	62.87	66.29

Table 3:

Autothermal cracking of ethane and ethane with butadiene over a Pt-Cu catalyst with a hydrogen to oxygen volume ratio of 0.5:1 (v/v).

	ethane butadiene	ethane butadiene	ethane butadiene	ethane butadiene
total feed rate nl/min	6.95	6.95	6.76	6.74
O ₂ : C ₂ H ₆ (v/v)	0.435	0.435	0.527	0.527
H ₂ :O ₂ (v/v)	0.546	0.542	0.474	0.477
N ₂ :O ₂ (v/v)	0.488	0.442	0.452	0.399
1,3-butadiene:ethane (v/v)	---	0.024	---	0.025
ethane conversion (%)	64.01	63.17	78.83	79.02
oxygen conversion (%)	98.43	98.42	98.63	98.64
butadiene conversion (%)	---	98.59	---	95.49
Ethene yield (g per 100g ethane feed)	43.84	45.62	50.63	51.80
Aromatics yield (g per 100g ethane feed)	0.01	0.05	0.08	0.08
Ethene selectivity (g per 100g ethane converted)	68.49	72.21	64.23	65.56

It can be seen from all the above examples that the ethene yield is generally increased and that in all cases with the addition of butadiene the ethene selectivity is increased. Furthermore it can also be seen that the addition of the butadiene does not result in any significant carbon formation on the catalyst surface due to the fact that only low amounts of aromatics are produced.

Example 4

The auto-thermal cracking catalyst comprising platinum and palladium deposited on alumina spheres (Catalyst B) was placed in the autothermal cracker and the cracker was heated to 550°C. Catalyst bed dimensions were 15mm diameter by 60mm deep

A feed stream comprising ethane, nitrogen and hydrogen was passed to the autothermal cracker. Oxygen was then passed to the autothermal cracker to initiate the reaction. The hydrogen to oxygen volume ratio was maintained at 0.7:1 (v/v). The reaction was performed at atmospheric pressure.

5 Samples were analysed at three oxygen : hydrocarbon feed ratios in the range 0.51-0.60 wt/wt.

Acetylene was then added at a level of 2.5vol% of acetylene in ethane and the analyses repeated.

10 The % conversion of ethane and the selectivity towards ethylene was measured and the results are shown in table 4 for the data at O₂:hydrocarbon (ethane plus acetylene) weight ratios of ca. 0.51, 0.56 and 0.60.

15 It can be seen from Table 4 that the ethene yield and selectivity are both increased with the addition of acetylene. Furthermore it can also be seen that the addition of the acetylene does not result in any significant carbon formation on the catalyst surface due to the fact that only low amounts of aromatics are produced.

20 In addition, and surprisingly, methane yield is observed to fall on addition of acetylene. It might be expected that the methane yield would increase since methane is a secondary product of the dehydrogenation / cracking reaction of ethane to produce ethylene. Thus, the presence of acetylene appears to inhibit methane formation.

Table 4:

Autothermal cracking of ethane and ethane with acetylene over a Pt-Pd catalyst with an hydrogen to oxygen volume ratio of 0.7:1 (v/v).

	Ethane ethane plus acetylene	ethane ethane plus acetylene	ethane ethane plus acetylene	ethane ethane plus acetylene
total feed nl/min	6.02	6.00	5.98	5.96
O2/C2H6 (v/v)	0.488	0.502	0.526	0.541
H2:O2 (v/v)	0.701	0.701	0.699	0.699
N2:O2 (v/v)	0.598	0.592	0.582	0.574
acetylene: ethane (v/v)	---	0.026	---	0.026
O2/hydrocarbon (wt/wt)	0.520	0.524	0.561	0.565
ethane conversion (%)	67.5	73.1	73.8	78.5
oxygen conversion (%)	99.4	99.3	99.4	99.4
Ethene yield (g per 100g ethane feed)	45.17	50.41	48.13	52.62
Methane yield (g per 100g ethane feed)	4.02	3.96	4.90	4.74
Aromatics yield (g per 100g ethane feed)	0.000	0.009	0.000	0.010
Ethene selectivity (g per 100g ethane converted)	67.0	69.0	65.2	67.1

Example 5

An auto-thermal cracking catalyst comprising platinum (two blocks of catalyst comprising 3wt% platinum) was placed in the autothermal cracker and the cracker was heated to 800°C.

A feed stream comprising n-pentane, nitrogen and hydrogen was passed to the autothermal cracker. Oxygen was then passed to the autothermal cracker to initiate the reaction. The hydrogen to oxygen volume ratio was maintained at 0.5:1 (v/v). The reaction was performed at atmospheric pressure.

Samples were analysed at oxygen to pentane feed ratios of 0.752, 0.675 and 0.636.(v/v).

An aromatic containing feedstream comprising xylene and indene at a weight ratio of 4:1 xylene:indene was then introduced to give a total aromatics to n-pentane ratio of 0.078 wt/wt.

The % conversion of n-pentane and the selectivity towards ethene was measured and the results are shown in table 5.

It can be seen from Table 5 that the ethene yield and selectivity are both increased with the addition of aromatic compounds.

Table 5:

Autothermal cracking of n-pentane and n-pentane with aromatics over a Pt catalyst with a hydrogen to oxygen volume ratio of 0.5:1 (v/v).

	pentane	pentane	pentane	pentane	pentane	pentane
	aromatic	aromatic	aromatic	aromatic	aromatic	aromatic
total feed rate nl/min	3.33	3.21	3.17	3.12	3.08	3.00
O ₂ /C ₅ H ₁₂ (v/v)	0.752	0.898	0.675	0.853	0.636	0.786
H ₂ :O ₂ (v/v)	0.504	0.500	0.505	0.500	0.505	0.505
N ₂ :O ₂ (v/v)	0.383	0.335	0.445	0.346	0.472	0.384
aromatic:pentane (wt/wt)	---	0.078	---	0.078	---	0.078
pentane conversion (%)	84.21	83.06	79.60	79.60	76.56	77.16
oxygen conversion (%)	98.17	97.74	98.28	97.80	98.37	97.90
aromatics conversion (%)	---	66.97	---	62.56	---	60.81
Ethene yield (g per 100g pentane feed)	33.49	33.53	30.47	31.52	28.68	29.86
Ethene selectivity (g per 100g pentane converted)	39.77	40.37	38.28	39.59	37.46	38.70

Printed: 14/01/2005

CLMSPAMD

GB 04722

JC05 Rec'd PCT/PTO 03 OCT 2005

9966(2)

10/551779

Claims:

1. A process for the production of olefins which process comprises feeding (i) a paraffinic hydrocarbon-containing feedstock, (ii) ~~at least one unsaturated hydrocarbon~~ and (iii) a molecular oxygen-containing gas to an autothermal cracker, wherein they are reacted in the presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising olefins, characterised in that at least one unsaturated hydrocarbon is co-fed with the paraffinic hydrocarbon feed and the molecular oxygen-containing gas to the autothermal cracker, and wherein the unsaturated hydrocarbon has a weight percentage of between 1-20wt% based on the weight of paraffinic hydrocarbon.
2. A process according to claim 1, wherein the unsaturated hydrocarbon is one or more of an alkene, an aromatic compound, a diene and an alkyne.
3. A process according to claim 2, wherein the unsaturated hydrocarbon is 1,2 butadiene, 1,3 butadiene, 2 methyl 1,3 butadiene, 1,3 pentadiene, 1,4 pentadiene and/or cyclopentadiene, preferably 1,3 butadiene.
4. A process according to claim 2, wherein the unsaturated hydrocarbon is acetylene, propyne and/or a butyne, preferably acetylene.
5. A process according to claim 2, wherein the autothermal cracker is operated at a total pressure of greater than 5 barg and the unsaturated hydrocarbon is benzene and/or toluene.
6. A process according to any one of the preceding claims wherein the unsaturated hydrocarbon fed to the autothermal cracker comprises at least one unsaturated hydrocarbon other than an alkene, such as at least one of a diene and an alkyne, and less

Printed: 14/01/2005

CLMSPAMD

GB 04722

than 1wt%, such as less than 0.5wt%, of total alkenes, based on the weight of paraffinic hydrocarbon fed to the reactor.

7. A process according to any one of the preceding claims wherein the unsaturated hydrocarbon derives from the product stream of a steam cracking reactor, the off gas stream of a fluid catalytic cracking reactor, the off gas streams of a delayed coker unit, a visbreaker unit or an alkylation unit or from a plastics recycling process, such as pyrolytic polymer cracking.
8. A process according to any one of the preceding claims wherein the unsaturated hydrocarbon fed to the autothermal cracking reactor derives from the autothermal cracking product stream.
9. A process according to claim 8, which process comprises the steps of:
 - (a) feeding a paraffinic hydrocarbon-containing feedstock and a molecular oxygen-containing gas to an autothermal cracker wherein they are reacted in the presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising olefins
 - (b) recovering at least a portion of the olefins produced in step (a) and
 - (c) recycling at least one unsaturated hydrocarbon produced in step (a) back to the autothermal cracker.
10. A process according to claim 9 which process comprises the steps of:
 - (a) feeding a paraffinic hydrocarbon-containing feedstock and a molecular oxygen-containing gas to an autothermal cracker wherein they are reacted in the presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising ethene and/or propene
 - (b) separating the hydrocarbon product stream produced in step (a) into a first stream comprising hydrocarbons containing less than 4 carbon atoms and a second stream comprising hydrocarbons containing at least 4 carbon atoms, including at least one unsaturated hydrocarbon containing at least 4 carbon atoms
 - (c) recovering ethene and/or propene from the first stream and
 - (d) recycling at least a portion of the second stream to the autothermal cracker.
11. A process according to claim 10 wherein the unsaturated hydrocarbon containing at least 4 carbon atoms is selected from 1,2 butadiene, 1,3 butadiene, 2

methyl 1,3 butadiene, 1,3 pentadiene, 1,4 pentadiene and cyclopentadiene, and preferably is 1, 3 butadiene.

12. A process according to claim 9 which process comprises the steps of:

- 5 (a) feeding a paraffinic hydrocarbon-containing feedstock and a molecular oxygen-containing gas to an autothermal cracker wherein they are reacted in the presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising ethene and/or propene, and at least one alkyne
- 10 (b) recovering at least a portion of the ethene and/or propene produced in step (a) and
- (c) recycling at least a portion of the at least one alkyne produced in step (a) back to the autothermal cracker.

13. A process for the production of olefins which process comprises feeding a paraffinic hydrocarbon, at least one unsaturated hydrocarbon and a molecular oxygen-containing gas to an autothermal cracker wherein they are reacted in the presence of a catalyst capable of supporting combustion beyond the normal fuel rich limit of flammability to provide a hydrocarbon product stream comprising olefins, said process being characterised in that the total hydrocarbon fed to the autothermal cracker comprises at least 20wt% of unsaturated hydrocarbons.
- 15

- 20 14. The process according to claim 13 wherein the total hydrocarbon fed to the autothermal cracker comprises at least 10wt% olefins and at least 10wt% aromatics.

25

30


22

Empf.zeit: 10/01/2005 16:25

Empf.nr.: 993 P.010

1/1

Fig.1



INTERNATIONAL SEARCH REPORT

In: onal Application No

PCT/GB2004/001278

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C07C5/333 C10G11/00 C10G11/22 C07C11/02 C07C11/04
C07C11/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C07C C10G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, CHEM ABS Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 529 793 A (BRITISH PETROLEUM CO PLC) 3 March 1993 (1993-03-03)	1,2,5,7
Y	*abstract; pages 2 and 3; example 3 and the claims*	1-14
X	BRIDGES R S ET AL: "RECYCLE BUTENES TO CRACKING" November 1986 (1986-11), HYDROCARBON PROCESSING, GULF PUBLISHING CO. HOUSTON, US, PAGE(S) 71-74 , XP001048615 ISSN: 0018-8190 the whole document	1-14
X	EP 1 001 001 A (NOVA CHEM INT SA) 17 May 2000 (2000-05-17) *abstract; passages 2, 32 and 35 and the claims*	1-14

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not
considered to be of particular relevance"E" earlier document but published on or after the international
filing date"L" document which may throw doubts on priority claim(s) or
which is cited to establish the publication date of another
citation or other special reason (as specified)"O" document referring to an oral disclosure, use, exhibition or
other means"P" document published prior to the international filing date but
later than the priority date claimed"T" later document published after the international filing date
or priority date and not in conflict with the application but
cited to understand the principle or theory underlying the
invention"X" document of particular relevance; the claimed invention
cannot be considered novel or cannot be considered to
involve an inventive step when the document is taken alone"Y" document of particular relevance; the claimed invention
cannot be considered to involve an inventive step when the
document is combined with one or more other such docu-
ments, such combination being obvious to a person skilled
in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

1 July 2004

Date of mailing of the international search report

14/07/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Lorenzo Varela, M.J.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB2004/001278

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 044 068 A (KURTZ BRUCE E) 23 August 1977 (1977-08-23) *abstract; column 5, lines 7-9 and the claims* -----	1-14
X	US 5 981 818 A (PURVIS DAVID ET AL) 9 November 1999 (1999-11-09) *abstract; column 3, lines 14-17; column 11, lines 18-25, column 18, lines 54-57 and the claims* -----	1-14
Y	US 6 395 944 B1 (GRIFFITHS DAVID CHARLES ET AL) 28 May 2002 (2002-05-28) *abstract; column 5 and the claims* -----	1-14
Y	WO 94/04632 A (BP CHEM INT LTD) 3 March 1994 (1994-03-03) the whole document -----	1-14

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/GB2004/001278

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0529793	A	03-03-1993	AT 137794 T 15-05-1996
			AU 648678 B2 28-04-1994
			AU 1953392 A 11-02-1993
			CA 2073850 A1 10-02-1993
			CN 1069483 A ,B 03-03-1993
			CZ 9202443 A3 17-02-1993
			DE 69210508 D1 13-06-1996
			DE 69210508 T2 12-09-1996
			DK 529793 T3 30-09-1996
			EP 0529793 A2 03-03-1993
			ES 2086073 T3 16-06-1996
			FI 923403 A 10-02-1993
			GR 3019870 T3 31-08-1996
			JP 3190129 B2 23-07-2001
			JP 5213780 A 24-08-1993
			KR 199684 B1 15-06-1999
			MX 9204605 A1 01-02-1993
			NO 923096 A 10-02-1993
			NZ 243526 A 26-08-1993
			SG 50368 A1 20-07-1998
			US 5382741 A 17-01-1995
			ZA 9205227 A 13-01-1994
EP 1001001	A	17-05-2000	US 6111156 A 29-08-2000
			EP 1001001 A1 17-05-2000
US 4044068	A	23-08-1977	BE 847225 A1 31-01-1977
			DE 2645766 A1 21-04-1977
			FR 2327976 A1 13-05-1977
			GB 1526847 A 04-10-1978
			IT 1070297 B 29-03-1985
			NL 7611207 A 18-04-1977
US 5981818	A.	09-11-1999	NONE
US 6395944	B1	28-05-2002	AU 751027 B2 08-08-2002
			AU 5642199 A 03-04-2000
			BR 9913555 A 05-06-2001
			EP 1129056 A1 05-09-2001
			WO 0015587 A1 23-03-2000
			US 2002143220 A1 03-10-2002
WO 9404632	A	03-03-1994	AT 148914 T 15-02-1997
			AU 4727193 A 15-03-1994
			BG 99508 A 31-01-1996
			BR 9306931 A 12-01-1999
			CN 1090566 A 10-08-1994
			CZ 9500373 A3 18-10-1995
			DE 69308145 D1 27-03-1997
			DE 69308145 T2 28-05-1997
			EP 0656044 A1 07-06-1995
			WO 9404632 A1 03-03-1994
			HR 931121 A1 31-12-1994
			HU 71164 A2 28-11-1995
			PL 307559 A1 29-05-1995
			RO 116907 B1 30-07-2001
			RU 2115692 C1 20-07-1998
			SI 9300441 A 31-03-1994

Information on patent family members

PCT/GB2004/001278

WO 9404632	A	SK	23195 A3	11-07-1995
		US	5625111 A	29-04-1997
		ZA	9306019 A	17-02-1995